

Fanless Slim PC with Intel Atom Dual Core processor

The Shuttle Slim PC XS3601B is an extremely slim and ergonomic Mini PC that works highly energy-efficiently. With a power consumption that is barely worth mentioning, and because of its completely fanless case layout, it is virtually maintenance-free and noiseless. This PC platform is powered by an Intel Atom D2550 dual-core processor (2x 1.86 GHz) with integrated GMA 3650 graphics. It sports an array of connectors too which include HDMI 1.3, DVI-D, D-Sub (VGA), 5x USB, Gigabit-LAN, WLAN, card reader, audio ports and two RS232 COM ports for business and vertical Markets. The operating system and storage can be configured to meet individual requirements. Shuttle offers a 'Pick-up-and-Return' service for 24 months after the date of purchase, as well as a free, Europe-wide hotline.

Slim PC System (BTO) **XS3601B**



Feature Highlights

Chassis	<ul style="list-style-type: none"> Slim 1.1 litre chassis Dimensions: 20 x 16 x 3.6 cm Hole for the Kensington Lock Optional VESA mount (PV03)
Operating system	<ul style="list-style-type: none"> Windows 7 Home Premium / Professional (32 bit) Available in EN, DE, FR, ES, IT, NL, DK
CPU	<ul style="list-style-type: none"> Intel Atom D2550 Dual Core (1.86 GHz)
Chipset	<ul style="list-style-type: none"> Intel NM10 Express Chipset
Graphics	<ul style="list-style-type: none"> Integrated Intel GMA3650 Graphics Shared Memory: max. 384MB DVMT
Memory	<ul style="list-style-type: none"> 2 or 4 GB DDR3 SO-DIMM memory
Storage	<ul style="list-style-type: none"> SATA hard disk or SSD (2.5") Built in SD card reader
Connectors and WLAN	<ul style="list-style-type: none"> HDMI v1.3 (supports digital audio) DVI-D D-Sub VGA 5x USB 2.0 (1x front, 4x rear) Microphone input Headphones output (Line-out) Gigabit-LAN 2x RS232 COM-Ports WLAN 802.11 b/g/n
Power supply	<ul style="list-style-type: none"> External 40W fanless power supply
Applications	<ul style="list-style-type: none"> Basic and Home-Media

Images are only for illustration purposes.



©2012 by Shuttle Computer Handels GmbH (Germany). All information subject to change without notice. Pictures for illustration purposes only.

Shuttle Slim PC XS 3601B - Product Features



Point of sales with Shuttle XS 3601B




Ideal for professional applications

Designed as a space-saver, this sleek 1.3 litre nettop PC only measures 3.3 cm in width. It maximizes space whether it is placed upright using its stand or affixed to the back of a display with the optional VESA mounting kit. Due to its small size and flexible design, this practical nettop offers exceptional functionality. It is well-suited for professional applications like digital signage, POS system, POI terminals, control PC or office PC (e.g. thin client). Thanks to the serial ports you can connect appropriate POS displays, cash register drawer or digital sensors. It is also possible to add an internal USB stick as a low cost storage device.

Fanless and quiet

The Shuttle Slim PC XS 3601B comes totally fanless making it perfect to be used in noise-sensitive environments such as living rooms, hospitals, libraries etc. As an additional benefit, fanless cases rarely gather dust on the inside and stay cleaner than others. So it's not only quiet and low in energy use, but also dust-free and virtually maintenance free.



The Atom processor integrates the graphics controller

Shuttle XS 3601B is equipped with Intels Atom D2550 processor (1,86 GHz, codenamed Cedarview). It comes with both the memory controller and graphics core on-die which helps to keep heat dissipation and memory latency low. The CPU is connected to the Southbridge NM10, codenamed Tiger Point.

Dual Core. Do more.

Shuttle always uses the dual-core variant of Intel's Atom processors and thus integrates the Atom D2550. This boosts the system performance significantly with particular regards to multi-threaded applications.



Highly energy-saving

The XS 3601B barely consumes, depending on system load, about 16~25 Watts. Running the device*) 5 days a week for eight hours a day, the annual consumption would amount to less than 40kWh which would mean just 8 Euros on the power bill (20 Euro ct/kWh) - way less than a conventional desktop PC draws.

*) Based on a configuration with 2GB of memory, 320GB hard disk and Windows 7 32 bit.



Supports two displays

The integrated graphics supports multiple display support on up to two separate monitors via HDMI, DVI-D and D-Sub/VGA. This improves the capabilities and productivity of the user by allowing them to spread multiple windows over two monitors and view them simultaneously.



SD card reader

The built-in SD card reader at the front side makes it easy to transfer files from your camera so you can share videos and photos on your XS 3601B with ease.



Kensington Lock

This is a small, metal-reinforced hole as part of an anti-theft system. As known from notebooks, this Mini-PC can also be safely locked by tying it to a solid object.

(The lock-and-cable apparatus is not included.)



Tiny power adapter

The external 40W power adapter is virtually noiseless and can easily be hidden behind the desk thanks to its tiny dimensions.

Dimensions: 89.5 x 37 x 26.5 mm (LWH) = 88ml



Two serial RS-232 ports (COM)

XS 3601B features two serial RS232 COM ports in the front panel. Today, many consumer PCs do no longer have this legacy port, since that interface has been superseded by USB. Still, they are commonly used for applications of industrial automation systems, scientific analysis, and POS systems.



Optional VESA mount (Accessory PV03)

Its optional VESA75/100 wallmount allows it to be installed on to walls or just affixed on the rear side of a monitor which is particularly interesting for the industry segment, company buildings and public institutions.



24/7 nonstop operation

Shuttle XS 3601B is officially approved for 24/7 permanent operation. Thanks to its low power consumption and completely passively cooling, this PC runs highly reliable making it perfectly suitable for digital signage and POI/POS applications.

Conditions for permanent use:

- Ambient temperature while under load: 5-35°C
- Air humidity while under load: 10-90% (not condensing)
- Free circulation of air amongst the PC must be guaranteed
- Ventilation holes must be clear
- If a hard disk is installed, this must also be approved for permanent operation by its manufacturer (max. one hard disk)



Note on operating position

Please make sure the system is always placed upright using either its stand or the optional VESA mount (PV03). Ventilation holes must not be blocked to ensure sufficient cooling.

Shuttle Slim PC XS 3601B Specifications

<i>Fanless and silent</i>	<p>Passive cooling, no fan noise at all Perfect to be used in noise-sensitive environments Fanless, dust-free and thus virtually maintenance-free</p>
<i>Low current</i>	<p>Power consumption: ca. 16W (idle mode) and ca. 25W (full load)</p>
<i>Chassis</i>	<p>Dimensions without Stand: 20 x 16 x 3.6 cm (DxHxW) = 1.15 litres Weight: 1.6 kg net, 2.3 kg gross Hole for the Kensington Lock at the back panel Optional accessory: 75mm and 100mm VESA mounting kit (PV03)</p>
<i>Operation System</i>	<p>Microsoft Windows 7 Home Premium or Professional, 32 bit version 6 languages available: German, English, French, Dutch, Italian, Spanish, Danish</p>
<i>Processor</i>	<p>Intel Dual Core Atom processor D2550 (Codename: Cedarview) Intel Hyper-Threading technology: 2-threads per core 32 nm manufacturing process, FCBGA559 package Intel 64 architecture, Core clock: 1.86 GHz L2 Cache: 1024kB , TDP: max. 10W Supports SSE2, SSE3, SSSE3, Execute Disable Bit Integrated North Bridge with controller for memory and graphics</p>
<i>Cooling</i>	<p>Passive, completely fanless cooling through convective heat transfer Warning: Please make sure the system is always placed upright using either its stand or the optional VESA mount. Ventilation holes must not be blocked to ensure sufficient cooling.</p>
<i>Chipset</i>	<p>Intel® NM10 Express Chipset (south bridge) Platform Controller Hub (PCH) Code name: Tiger Point</p>
<i>BIOS</i>	<p>AMI BIOS in a 8Mbit Flash ROM supports PnP, ACPI 2.0 Supports external USB flash memory card boot up Supports Power fail resume / AC power on state / always on / always off Supports Wake-on-LAN (WOL) from S3, S3, S5 ACPI states Supports Unified Extensible Firmware Interface (UEFI)</p>
<i>Memory</i>	<p>2 or 4 GB DDR3 SO-DIMM memory</p>
<i>Hard disk drive or SSD</i>	<p>SATA hard disk or SSD in 6.35cm/2.5" format</p>

<p><i>Integrated Graphics</i></p>	<p>The Graphics Processing Unit (GPU) is integrated into the processor Intel GMA 3650, Graphics Base Frequency: 640 MHz Supports DirectX 9 Maximum shared memory: 8MB pre-allocated plus 384MB Video Memory Technology (DVMT) Three video outputs: HDMI v1.3, DVI-D and D-Sub (VGA) Two outputs can be used at the same time. Supports dual display in clone or extended mode. HDMI and DVI support the Intel HDCP function (High bandwidth Digital Content Protection) HDMI/DVI display resolution up to 1920x1200.</p>
<p><i>Integrated Audio</i></p>	<p>Integrated Audio IDT92HD81 Audio Codec with Azalia support Two analog audio connectors (3.5mm): 1) Line out (head phone) 2) microphone input Supports digital 7.1 HD audio via the HDMI port.</p>
<p><i>Card Reader</i></p>	<p>Integrated card reader supports SD, SDHC and SDXC memory flash cards</p>
<p><i>Wired Network</i></p>	<p>RJ45 connector supports Gigabit LAN at 10/100/1000 Mbit/sec. Network controller Realtek RTL8411 Supports Wake-on-LAN (WOL) from S3, S3, S5 ACPI states</p>
<p><i>Wireless Network</i></p>	<p>Supports IEEE 802.11b/g/n, max. 150Mbps up-/downstream Security: WPA/WPA2(-PSK), WEP 64/128bit, IEEE 802.11x/i Half size Mini-PCIe-Card</p>
<p><i>Connectors</i></p>	<p>HDMI v1.3 digital video and audio output DVI-D digital video output D-Sub/VGA analog video (15 pin) 5x USB 2.0 (1x front, 4x rear) Gigabit network (LAN, RJ45) Audio Line-out (head phone) Microphone input 2x RS232 COM ports (front panel) DC input for the external power adapter</p>
<p><i>LEDs and buttons</i></p>	<p>Power button Power LED (white) Hard disk LED (blue)</p>
<p><i>Power supply</i></p>	<p>External 40W AC/DC power adapter (fanless), 19V / 2.1A AC Input: 100~240V AC, 50~60Hz Automatic voltage adjust Dimensions: 89.5 x 37 x 26.5 mm (LWH) DC Connector: 5.5/2.5mm (outer/inner diameter)</p>

©2012 by Shuttle Computer Handels GmbH (Germany). All information subject to change without notice. Pictures for illustration purposes only.

24/7 nonstop operation	<p>This device is approved for 24/7 permanent operation. Requirements:</p> <ul style="list-style-type: none"> - Free circulation of air amongst the PC must be guaranteed. - Ventilation holes must be clear. - If a hard disk is installed, this must also be approved for permanent operation by its manufacturer (max. one hard disk)
Environmental	<p>Operating temperature range: 0~35°C Relative humidity range: 10~90% (non-condensing)</p>
Certification and Compliance	<p>EMI: CE, FCC, BSMI, C-Tick, CCC Safety: CB, BSMI, ETL Other compliances: RoHS, Eup Lot6</p> <p>This device is classed as a technical information equipment (ITE) in class B and is intended for use in living room and office. The CE-mark approves the conformity by the EU-guidelines:</p> <ul style="list-style-type: none"> - EMV-guideline 89/336/EWG electromagnetic tolerance - LVD-guideline 73/23/EWG use of electric devices within certain voltage-limits

Comparison: Shuttle Slim-PC XS36VL Series (Barebone/System)

Model	Type	Processor	OS	Memory	HDD	Barcode
XS36VL	Barebone	Intel Atom D2550	-	-	-	UPC: 811686004301
XS36V-703L	System w/o OS	Intel Atom D2550	-	2 GB	320 GB	EAN: 4046047102617
XS3601B	System with OS	Intel Atom D2550	configurable			-
XS3601BA	System with OS	Intel Atom D2550	Win 7 Prof. 32 bit	2 GB	320 GB	EAN: 4046047102631

Comparison: Shuttle Slim-PC Barebone PC XS35/XS36 Series

Model	Graphics	HDMI	DVI	D-Sub	RS232	WOL	ODD [4]	Atom Processor	Memory	LAN
XS35	Intel GMA3150	-	-	Yes	-	-	Yes	D510 (1.66 GHz)	Max. 2GB DDR2-800 [6] 1x SO-DIMM	100
XS35GT	NVIDIA ION2	Yes	-	Yes	-	-	Yes			
XS35V2	Intel GMA3150	-	-	Yes	-	-	Yes	D525 (1.80 GHz)	Max. 4GB DDR3-800 [6] 1x SO-DIMM	Giga
XS35GT V2	NVIDIA ION2	Yes	-	Yes	-	-	Yes			
XS35GTA V2	ATI Mobility Rad. HD 5430	Yes	-	Yes	-	-	Yes			
XS35GS V2	ATI Radeon HD 7410M	Yes	-	Yes	-	-	Yes	Without "L": D2700 (2.13 GHz) "L"-version: [5] D2550 (1.86 GHz)	Max. 4GB DDR3-1066 [6]	Giga
XS35V3(L)	Intel GMA3650 [2]	Yes	-	Yes	-	Yes [3]	Yes			
XS35GTA V3 [1]	ATI Radeon HD 7410M	Yes	-	Yes	-	Yes [3]	Yes			
XS35GS V3L	ATI Radeon HD 7410M	Yes	-	Yes	-	Yes [3]	Yes			
XS36V(L)	Intel GMA3650 [2]	Yes	Yes	Yes	2x	Yes [3]	-	D2550 (1.86 GHz)	2x SO-DIMM	

[1] **XS35GTAV3** is also called **XS35GS V3** outside EU.

[2] Intel offers sophisticated graphics driver for the integrated **Intel GMA3650** graphics only for Windows 7 32 bit. Linux can be used in standard mode without video and 3D acceleration. (date Oct. 2012)

[3] Supports Wake-on-LAN (WOL), Power fail resume (always on/off) and Resume by RTC Alarm

[4] "ODD" means 5.25" bay for an optical drive in slim-line format

[5] In 2012, Intel phased out the Atom D2700 processor and introduced the D2550 as its successor. This new model comes with a slightly reduced clock rate, while any other features are maintained.


[6] DDR3-1333 is supported at DDR3-1066 or DDR3-800 clock rate, respectively.

Shuttle Slim PC XS 3601B – Connectors

Front Panel



Back Panel



- 1 Power button
- 2 Power LED
- 3 Hard disk LED
- 4 2x RS232 COM ports
- 5 SD card reader
- 6 Vertical stand
- 7 USB 2.0 connector

- A Microphone input
- B Head phone output (Line out)
- C Gigabit LAN connector (RJ45)
- D 4x USB 2.0 connectors
- E DVI-D connector
- F Vertical stand
- G Hole for the Kensington-Lock
- H HDMI connector
- I D-Sub/VGA connector
- J Connector for the power adapter



Warning:

Please make sure the system is always placed upright using either its stand or the optional VESA mount (PV03). Ventilation holes must not be blocked to ensure sufficient cooling.