

Silent 300W Power Supply Unit with 80PLUS Certification

The PC60 provides the additional power needed to satisfy the demands of high power graphics cards and large capacity storage devices. The 80PLUS logo identifies PC60 as a modern product with at least 80% energy-efficiency whereas other power supplies range from 65-75% efficiency. It is the optimal solution for power users wanting to upgrade without compromising the efficiency, stability, low-noise, and portability of the XPC.

XPC Accessory **PC60**



Feature Highlight

Input	<ul style="list-style-type: none"> Input Voltage: 100~240V AC Input Current: 6A / 3A (100/240V AC) Frequency: 60~50 Hz Active PFC (Power Factor Correction)
Output	<ul style="list-style-type: none"> Total combined output (3.3/5/12V): 300W Total combined output (3.3/5V): 90W Max. Current: 3.3V: 14.5A / 5V: 15A / 12V: 2x 14A / -12V: 0.3A / 5VSB: 2A Hold up time: >17ms (full load, 115V AC) +12V Rise time: <20ms (full load) Short circuit protection (SCP): latch off Other protection: OTP, OPP, UVP, OCP Power good signal: TTL compatible +5V Standby at 2.0A +3.3V Remote sensing
Energy efficiency	<ul style="list-style-type: none"> 80 PLUS logo: at least 80% efficient at 20%, 50%, and 100% loads aligns to the power supply requirements of Energy Star 4.0
Connectors	<ul style="list-style-type: none"> Mainboard ATX 4 pin (12V) + 20 pin 1x FDD, 3x S-ATA, 2x Molex Cable length designed for the XPC
Environmental	<ul style="list-style-type: none"> Operating Temperature: 10~50°C Storage Temperature: -40~70°C MTBF: >100.000 hours (75% load, 25°C) Noise: <30dB at 50cm for 200W Load
Safety/EMI	<ul style="list-style-type: none"> FCC class B, CE, BSMI, CCC
Other	<ul style="list-style-type: none"> Dimension: 190 x 82 x 43 mm (l x w x h) Weight: 0.9kg net, 1.0kg gross
Compatibility	<ul style="list-style-type: none"> Compatible with XPC chassis G, G2, G5, G6 and the models ST61G4, D10, D1416S, K45 and K48, but it is NOT compatible with SD11G5, S558G2, SK83G, SN85G4, SN95G5, ST20G5.



**ATX
20 pin**



**ATX 12V
4 pin**



**1x
Floppy**



**2x
Molex**



**3x
S-ATA**



8 116860 052232